

Flexible Aluminum Conduit

Coils and Reels



Features

- Corrosion and crush resistant
- Lightweight, easy to cut
- Smooth interior for easy wire pull through
- Easy to follow contours

Applications

- For use as an electrical raceway in close quarters requiring extra flexibility; one-third the weight of steel
- For use with Topaz UL listed connectors 3-1/2" thru 4" HWA

Standard Material

- Aluminum alloy construction, with tempered alloy for maximum strength

Coils

Catalog Number	UPC	Size	Feet/Coil	Ship Case	Weight/Case	Inside Diameter		Outside Diameter	
						Min.	Max.	Min.	Max.
4300	86366	3/8"	250'	250	14	.374	.392	.559	.609
4300C100	86367	3/8"	100'	100	6	.374	.392	.559	.609
4301	86368	1/2"	100'	100	10	.625	.644	.859	.92
4302	86369	3/4"	100'	100	14	.811	.835	1.044	1.105
4303	86370	1"	50'	50	11	1	1.04	1.30	1.379
4304	86371	1-1/4"	50'	50	11	1.25	1.30	1.55	1.629
4305	86372	1-1/2"	25'	25	12	1.50	1.573	1.85	1.95
4306	86373	2"	25'	25	12	2	2.079	2.35	2.45
4307	86374	2-1/2"	25'	25	14	2.50	2.70	2.859	3.059
4308	86375	3"	25'	25	16	3	3.20	3.359	3.559
4309	86376	3-1/2"	25'	25	22	3.50	---	3.859	4.059
4310	86377	4"	25'	25	25	4	---	4.359	4.559

Reels

Catalog Number	UPC	Size	Feet/Reel	Ship Case	Weight/Case	Inside Diameter		Outside Diameter	
						Min.	Max.	Min.	Max.
4300R	86378	3/8"	1000'	1000	84	.374	.392	.559	.609
4301R	86379	1/2"	1000'	1000	118	.625	.644	.859	.92
4302R	86380	3/4"	500'	500	76	.811	.835	1.044	1.105
4303R	86381	1"	300'	300	74	1	1.04	1.30	1.379
4304R	86382	1-1/4"	200'	200	64	1.25	1.30	1.55	1.629
4305R	86383	1-1/2"	100'	100	41	1.50	1.573	1.85	1.95
4306R	86384	2"	100'	100	55	2	2.079	2.35	2.45